



EECSL-8000SR Red LED Exit Combo with Battery Backup  
 EECSL-8000SG Green LED Exit Combo with Battery Backup

## STANDARD FEATURES

### HOUSING

- ▶ Injection-molded thermoplastic ABS housing.
- ▶ UL 94V-0 flame rating.
- ▶ Innovative, snap-together design allows for fast installation.
- ▶ Replaceable directional chevron inserts are easily removed and reinserted.
- ▶ Letters 6" height with 3/4" stroke.
- ▶ Single or double face configuration.
- ▶ Two fully adjustable glare-free square shape light heads for emergency light.

### MOUNTING

- ▶ Wall or Ceiling mounting.
- ▶ Housing snaps to canopy with simple twist and locking tightly secure housing to canopy.

## ELECTRICAL FEATURES

### ELECTRICAL

- ▶ 120/277 VAC Dual voltage operation.
- ▶ Low power consumption - 3.8 watts at normal operation, 15 watts at emergency operation.
- ▶ LED indicator light and push button test switch.
- ▶ Remote capability - may power additional remote heads (up to 6V 12W) with additional battery.

### LAMPS

- ▶ LEDs mounted on print circuit board. (for Exit Sign)
- ▶ LED lamps are operating in normal (AC input) and emergency (DC input) modes.
- ▶ 2 X 6V 5.4 watts DC T5 wedge base lamps for emergency mode.

### BATTERY

- ▶ Lead-Calcium Battery (6V 4.5Ah).
- ▶ May use additional battery, when add remote light heads to the fixture. (Total 2 X 6V 4.5 Ah battery)
- ▶ Low voltage battery disconnection.

## ORDERING INFORMATION

Item No.	Panel Color	Housing Color	IR Test Option	Diagnostics	Application
EECSL-8000S	R: Red	W: White	IR1 : 30sec test	CT	DL: Damp location
	G: Green	B: Black	IR2: 30sec or 90min test		